


# Type 3 Internal Alarm Cable PVC to BS4737 - 3.30:2015



Cable Construction	4 , 6, 8, 12 Core	
Conductor	Tinned Copper Clad Aluminium	
Conductor Diameter	TCCA 0.19 +/-0.008	TCCA 0.19 +/-0.008
Stranded Diameter	0.61	0.61
Insulation	PVC	LSF
Thickness (mm)	0.20	0.20
Insulation Diameter (mm)	1.0+/-0.10mm	1.0+/-0.10mm
Insulation Colours from	Red - Blue - Turquoise - Black - Orange - White Brown - Pink - Yellow - Green - Violet - Grey	
ilisulation colours from		
Nylon Rip-Cord	210D	
Colour	yellow	
Jacket	PVC	LSF
Nominal Thickness	0.50mm	0.50mm
Diameter (mm) 6 Core	4 Core 3.50 ±0.20	4 Core 3.50 ±0.20
Diameter (mm) 8 Core	6 Core 4.00 ±0.20	6 Core 4.00 ±0.20
Diameter (mm) 12 Core	8 Core 4.20 ±0.20	8 Core 4.20 ±0.20
		12 Core 5.40 ±0.20
Jacket Colour	White or White or Brown	
Marking	001m100m	
Electrical Characteristics		
Max Conductor DC Resistance	20°C Ω/100m 155	
Minimum Insulation Resistance	20°C [MΩ/M] >200	
Rated Temperature	80°C	
Rated Voltage	30V	
<b>Outer Sheath Options</b>		
PVC	Polyvinyl Chloride	
LSF	Low Smoke and Fume	

Our Other Products Include

# **Coaxial Cable**

RG & URM Coaxial CCTV Coaxial Composite / Hybrid TV / Satellite

# Digital Coaxial

Cat5E UTP/FTP (100 MHz)
Cat6 UTP/FTP (250 MHz)
Cat6A U/FTP (500 MHz)
Cat7 S/FTP (600 MHz)

**Networking Cable** 

## **Data Cabinets**

Wall & Floor Standing Cabinets
Server Cabinets
Cabinet Accessories

#### **Alarm Cable**

TCCA

Premium BS4737

# **Belden Style Cable**

Single Pair Cable Overall Shielded Cores Overall Shielded Pairs Foil & Braid Shielded Pairs Individually Shielded Pairs Bus / Profi-Bus

# **Telecom Cable**

Budget Telecom CW1308 CW1128/98 Bell Wire

## **Speaker Cable**

Budget 13/42/79 Strands

Oxygen Free

## **Fire Resistant Cable**

Standard / Enhanced Mineral Insulated Accessories

## **Defence Standard**



